

# **SAFETY DATA SHEET**

## **Section 1: Product and Company Identification**

Product Identifier: PowerWeld Nuclear Cleaner/Remover
Product Use: Non-Destructive Dye Penetrant Cleaner

Item Code: PW1500

Supplier Name: PowerWeld Inc.
Supplier Address: 2501 Beech Street

Valparaiso, IN 46383

Supplier Web Address: www.powerweldinc.com

*Supplier Phone:* 219-462-8700

1-800-826-9073

Emergency Phone: CHEMTREC (24-Hour) 1-800-424-9300

Prepared By: PowerWeld Inc.
Preparation Date: 21 December 2020

OSHA Regulatory Status: Regulated WHMIS Classification: A, B-5, D-2B

## **Section 2: Hazard Identification**

Classification: Germ cell mutagenicity Category 1B
Carcinogenicity Category 1A

Aspiration toxicity Category 1
Flammable aerosols Category 1

Label Elements:



Signal Word (GHS) Danger

#### **Hazard Phrases**

H222 Extremely flammable aerosol

H304 May be fatal if swallowed and enters airways

H340 May cause genetic defects

H350 May cause cancer

## **Precautionary Phrases**

P301+ IF SWALLOWED:

P310 Immediately call a POISON CENTRE or doctor/physician.

P308+ IF EXPOSED OR CONCERNED: P313 Get medical advice/attention.

P3331 DO NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste

facility.

Other Hazards: May be harmful in contact with skin

#### Section 3: Composition/Information on Hazardous Ingredients

HAZARDOUS INGREDIENTS	CAS NUMBER	APPROXIMATE CONCENTRATION (%)
Petroleum Distillates	64742-89-8	80 - 90
Propane / Isobutane / N-Butane	68476-86-8	10 - 20

#### **Section 4: First-aid Measures**

*Inhalation:* Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration and transport to nearest medical facility for additional

treatment.

*Ingestion:* Do NOT induce vomiting. Call physician immediately. Never give anything

by mouth to an unconscious person. Risk of product entering the lungs on

vomiting after ingestion.

Eye Contact: Immediately flush upper and lower eyelids with plenty of water. After

initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Rest eyes for 30 minutes. If redness, burning, blurred vision or

swelling persists, visit nearest medical facility for additional treatment.

Skin Contact: Wash off immediately with soap and water. Do not use ointments. Wash

contaminated clothing before reuse. If skin irritation persists, contact a

physician.

*Symptoms:* Treat symptomatically.

NOTE: In all severe cases, contact physician immediately. Local telephone operators can provide number of regional poison control centre.

#### **Section 5: Fire-fighting Measures**

Flammable: Extremely flammable aerosol

Means of Extinction: Water fog; foam; dry chemical; alcohol-resistant foam; carbon dioxide

(CO<sub>2</sub>). Do not use a solid water stream as it may scatter and spread fire.

Auto-ignition Temperature: Not available
Hazardous Combustion Products: Carbon oxides

Explosion Data Sensitivity to

piosion Data sensitivity to

Mechanical Impact: Not available

Explosion Data Sensitivity to

Static Discharge:

Special Equipment: Not available

Precautions for Fire Fighters: As in any fire, wear self-contained breathing apparatus pressure-demand,

MSHA/NIOSH (approved or equivalent) and full protective gear.

## **Section 6: Accidental Release Measures**

Protective Equipment: See Section 8

Emergency Procedures: Beware of vapours accumulating to form explosive concentrations. Vapours

can accumulate in low areas.

Leak or Spill Procedure: Ensure adequate ventilation. Do not flush into surface water or sanitary

sewer system. Prevent further leakage or spillage if safe to do so. Use a non-combustible inert absorbent (ie. vermiculite, sand or earth, etc.) to soak up

the product and place into a container for proper disposal.

#### **Section 7: Handling and Storage**

Handling Procedures and Equipment: Avoid contact with eyes. Avoid breathing vapours or mists. Contents under

pressure. Do not puncture or incinerate cans. Do not stick pin or any other

sharp object into opening on top of can.

Storage Requirements: Store in area below 120°F (49°C). Do not incinerate or burn containers.

Ensure canister is in a secure place to prevent accidental puncture. Always

ensure canister is capped when not in use. Keep out of the reach of children.

Incompatibilities: Oxidizing agents

## **Section 8: Exposure Controls/Personal Protection**

Exposure Limits:

HAZARDOUS INGREDIENTS	CAS NUMBER	OSHA PEL	ACGIH TLV
Ethyl Benzene	100-41-4	100 ppm	20 ppm
Benzene	71-43-2	1 ppm	0.5 ppm

Engineering Controls: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn. Showers and/or eyewash

stations are recommended.

Personal Protective Equipment: Eyes - Safety glasses with side-shields. Where eye contact could occur,

chemical splash proof goggles are recommended.

 $\underline{Skin}$  - Wear impervious protective clothing, including boots, gloves, lab

coat, apron or coveralls, as appropriate, to prevent skin contact.

<u>General Hygiene</u> - Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash hands and face before breaks and immediately after handling the product. Avoid breathing

vapours, mist or gas.

#### **Section 9: Physical and Chemical Properties**

Physical State: Aerosol

Odor and Appearance: Clear colorless liquid with naphtha odor

Odor Threshold (ppm):

PH:

Neutral

Melting Point:

Not available

Freezing Point:

Not available

Not available

Not available

Flashpoint:

Flashpoint:

Vapour Pressure (mm):

Not available

141°F / -96.4°C

Vapour Density (Air = 1): 4.1, heavier than air

Upper Flammable Limit (% by volume): Not available Lower Flammable Limit (% by volume): Not available

#### **Section 10: Stability and Reactivity**

Percentage Volatility:

Chemical Stability: Stable under recommended storage conditions

100 %

Possible Hazardous Reactions: None under normal processing

Conditions to Avoid: Extreme temperatures and direct sunlight

Materials to Avoid (Incompatibilities): None known based on information supplied

Not available *Conditions of Reactivity:* Hazardous Decomposition By-Products: Hazardous Polymerization:

None known Does not occur

## **Section 11: Toxicological Information**

Skin Contact: Irritating to skin. Prolonged skin contact may defat or dry the skin and

produce dermatitis. May cause frostbite.

Skin Absorption:

Eye Contact: Irritating to eyes. Liquid or vapours may cause redness, burning, tearing,

swelling and/or pain.

Inhalation: Irritating to respiratory system. Avoid breathing vapors or mists.

Symptoms of overexposure are dizziness, headache, tiredness, nausea,

unconsciousness, cessation of breathing.

Ingestion: Not an expected route of exposure. Potential for asphyxiation if swallowed.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Not available *Effects of Acute Exposure: Effects of Chronic Exposure:* Not available

Health [1] Flammability [4] Physical Hazard [2] Personal Protection [B] Suggested HMIS Rating:

Suggested NFPA Rating: Health [1] Flammability [4] Stability [0]

Irritancy of Product: Not available Sensitization to Product: Not available

Carcinogenicity: There are no known carcinogenic chemicals in this product

Reproductive Effects: Not available Respiratory Sensitization: Not available Toxicological Data: Not available

## **Section 12: Ecological Information**

Aquatic and Terrestrial Toxicity: Not available Persistence and Degradability: Not available Bio accumulative Potential: Not available Soil Mobility: Not available

## **Section 13: Disposal Considerations**

NOTE: Always dispose of waste in accordance with local, provincial and federal regulations.

Safe Handling: Do not re-use empty containers. This product contains one or more

substances that are listed with the State of California as a hazardous waste.

Methods of Disposal: Material resulting from clean-up operations may be hazardous wastes and

therefore subject to local, regional and federal regulations.

## **Section 14: Transportation Information**

UN Identification Number:

Proper Shipping Name: Aerosols, Flammable Limited Quantity

Hazardous Class or Division: 2.1 Packing Group: None

#### **Section 15: Regulatory Information**

Toxic Substances Control Act (TSCA): SARA Title III, Section 313:

The product on this SDS, or all of its components, is listed under TSCA. The following ingredients are subject to the reporting requirements of Section 313 of Title III of the Superfund and Reauthorization Act of 1986 and 40 CFR Part 372: Xylene, Mixed Isomer (1330-20-7) <0.13%; meta-Xylene (108-38-3) <0.05%; Ethylbenzene (100-41-4) <0.1%; Benzene (71-43-2) <0.005%; Toluene (108-88-3) <0.1%, Naphthalene <0.002%

Comprehensive Environmental Response,

Compensation, and Liability Act

(CERCLA): VM&P Naphtha (64742-89-8) Reportable Quantity 66,667 lbs.

California Proposition 65: This material may contain trace amounts of chemicals known to the State of

California to cause cancer and/or birth defects and/or reproductive harm. The following ingredients appear of the Proposition 65 list(s): Ethyl Benzene (Carcinogen); Benzene (Carcinogen, Developmental & Male

Reproductive)

Pennsylvania Right to Know Information: (5 most predominant ingredients / hazardous & non-hazardous)

Petroleum Distillates

Canadian Workplace Hazardous

Materials Information System (WHMIS): This SDS has been prepared according to the hazard criteria of the

Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. WHMIS CLASS: Aerosol - A, B-5, D-2B

Domestic Substances List (DSL): The product on this SDS, or all of its components, is included in the DSL.

#### Section 16: Other Information

Preparation Date: 10 June 2016
Date of Last Revision: 21 December 2020

This SDS format is in accordance with GHS. PowerWeld Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of PowerWeld. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of enduser. No other warranties, expressed or implied, are made.